













Foto	Omschrijving	Kenmerken	Geschikt voor
	Hulpaardpennen (2 punten/1 set)		4105DL(H)/6516/6516BT/7272
	Cat. II standaardprobe		4300
	AC stroomtang	Ø 24 mm AC 100A ±2,0%uitl.±0,3mV (50/60Hz)	1051, 1052, 1061, 1062
	AC stroomtang	Ø 40 mm AC 500A ±2,0%uitl.±0,3mV (50/60Hz)	1051, 1052, 1061, 1062
	AC stroomtang	Ø 55 mm AC 1000A ±2,0%uitl.±0,3mV (50/60Hz)	1051, 1052, 1061, 1062
	AC laadstroomtang	Ø 68 mm AC 1000A ±0,5%uitl.±0,2mV (50/60Hz)	1051, 1052, 1061, 1062, 6305, 6315
	AC laadstroomtang	Ø 40 mm AC 500A ±0,5%uitl.±0,1mV (50/60Hz)	1051, 1052, 1061, 1062, 6305, 6315
	AC laadstroomtang	Ø 40 mm AC 200A ±0,5%uitl.±0,1mV (50/60Hz)	1051, 1052, 1061, 1062, 6305, 6315
	AC laadstroomtang	Ø 24 mm AC 100A ±0,5%uitl.±0,1mV (50/60Hz)	1051, 1052, 1061, 1062, 6305, 6315
	AC laadstroomtang	Ø 24 mm AC 5A ±0,5%uitl.±0,1mV (50/60Hz)	1051, 1052, 1061, 1062, 6305, 6315
	Flexibele laadstroomtang	Ø 150 mm AC 300/1000/3000A ±1,0%uitl. (45-65Hz)	6305, 6315
	Flexibele laadstroomtang	Ø 110 mm AC 1000A ±0,8%uitl.±0,2mV (50/60Hz)	6305, 6315