

SKU	KPSDCM300MINICBINT	KPSDCM350MINICBINT	KPSDCM450MINICBINT
KPS Model Name	DCM300MINI	DCM350MINI	DCM450MINI
Feature Summary			
Main Display	4000 Count	6000 Count	6000 Count
Backlight	no	√	√
Torchlight	no	√	√
Autoranging	√	√	√
Auto AC/DC Selection	no	no	no
True RMS	√	√	√
HFR(High Frequency Rejection)	no	no	no
AC Frequency Response	50 to 60Hz (A) and 45 to 500Hz (V)	50 to 60Hz (A) and 45 to 500Hz (V)	50 to 60Hz (A) and 45 to 500Hz (V)
ACA/DCA Capalibity	40.00A/400.0A/600.0A AC	60.00A/600.0A AC	60.00A/600.0A ACDC
ACV/DCV Capability	400.0mV/4.000V/40.00V/400.0V/600V	600.0mV/6.000V/60.00V/600V	600.0mV/6.000V/60.00V/600V
Ohm Capability	Up to 40MΩ	Up to 60MΩ	Up to 60MΩ
Smart Data Hold	no	no	no
DCA Zeroing	no	no	√
Diode/Continuity Test	√	√	√
Frequency Counter	no	Up to 60MHz	Up to 60MHz
Capacitance Capability	no	Up to 60mF	Up to 60mF
Temperature	no	Up to 1.000°C	Up to 1.000°C
Min/Max	no	no	no
REL	no	no	no
NCV(Non-Contact Voltage)	√	√	√
AutoV LoZ	no	no	no
Maximum Conductor Size			
Maximum Jaw Opening			
Auto Power Off	√	√	√
4 feet Drop Proof	√	√	√
Deluxe Carrying Case			
Safety	CAT III 600V/CAT IV 300V	CAT III 600V/CAT IV 300V	CAT III 600V/CAT IV 300V
Specification			
ACA Basic Accuracy	±(3%+8d)	±(3%+8d)	±(2%+8d)
DCA Basic Accuracy	N/A	N/A	±(2%+8d)
ACV Basic Accuracy	±(1%+3d)	±(1%+3d)	±(1%+3d)
DCV Basic Accuracy	±(0.5%+3d)	±(0.5%+3d)	±(0.5%+3d)
AutoV LoZ Basic Accuracy	N/A	N/A	N/A
Ω Basic Accuracy	±(1%+3d)	±(1%+3d)	±(1%+3d)
Frequency Basic Accuracy	N/A	±(0.5%+2d)	±(0.5%+2d)
Capacitance Basic Accuracy	N/A	±(3%+5d)	±(3%+5d)